

PDA-GS0331W

3.5" MTK6761 Quad-Core
PDA Handheld Terminal



Features:

- MT6761V/WE 4 core*A53@1.8GHZ
- 4GB+64GB
- 3.5inch Resolution 480*320 Capacitive
- Android 12.0, Support google play store
- Battery capacity 5200mAh
- Optional Honeywell 5703/Zebra SE5500 (10M~12M), 2D Scanner

Specifications:

Performance

Chipset	MTK6761 Quad-Core	OS	Android 12.0, support Google Play
RAM	4GB	Power Supply	5200mAh Battery, Removable Battery
ROM	64GB		

Display

LCD	3.5" IPS	Touch Screen	Capacitive Multi-touch Screen
Resolution	480*320		

I/O Interface and Sensor

USB	1 x TYPE-C,Support fast charging 9V 1.67A	Key button	Support
Camera	Rear camera 8MP (optional 13MP)	vibration motor	Support
SIM card slot	NANO 4G Dual SIM Card Slot	PDA receiver	Support
Sensor	Gravity sensor/Proximity sensor/Light sensor (optional Gyroscope/Electronic compass)	Scanner 2D	Optional Honeywell 5703/Zebra SE5500 (10M~12M)
flashlight	Support	NFC	Support
UWB	Optional		

Wireless Communication

4G	GSM: 2/3/5/8 ; WCDMA(B1,B2,B5,B8) TDD: 34/38/39/40/41 FDD- LTE(B1,B2,B3,B5,B7,B8,B19,B20)	WIFI	802.11 a/b/g/n, 802.11n/ac
		BLUETOOTH	BT 5.0
		GNSS	support AGPS GPS BEIDOU,GLONASS

Environmental Specifications

operating temperature	-20°C ~ 55°C	storage temperature	-40°C ~ 70°C
Operating humidity	5%~95% (No condensation)	Impact temperature	-20°C ~ 60°C, turn off PDA, Continue to do test 4 hours (2 hours at high temperature, 2 hours at low temperature) with 5 cycles optional
810H	Support	Cold chain environment	
Drop height	1.8 M, Twice for each of the 6 sides and 8 angles	device size	193mmx67mmx26mm
Roll testing	1m 1000 times	packing size	203.5x166x39
ESD	air discharge ±15kV, Contact discharge ±8kV	Weight of device	355g
IPXX	IP65	color	black

Standard

TYPE-C Cable, Hand Strap, Adaptor

Product's Six Views:

