

PDA-GS0651W

5.7" MT6762 Octa-Core 2.0GHz Processor
PDA Handheld Terminal



Features:

- MT8791V/TZA, 6nm process, 8-core processor, 2 * A78 2.6G+6 * A55 2.0G
- 8G+128G or 8G+256G (optional 12+512G)
- 6.72" 1080*2400 Capacitive Multi-touch
- Android 14 support Google Play
- 6000mAh Detachable Battery
- Optional 2D scanning, Zebra SE-4710/SE5500
- IP67 Protection Level

Specifications:

Performance			
Chipset	MT8791V/TZA, 6nm process, 8-core processor, 2 * A78 2.6G+6 * A55 2.0G	OS	Android 14, support GMS
RAM/ROM	8G+128G or 8G+256G (optional 12+512G)	Power Supply	Standard 6000mAh, detachable battery (optional 12000mAh)
Display			
LCD	6.72"	Touch Screen	Capacitive Multi-touch Screen
Resolution	1080*2400		
I/O Interface and Sensor			
USB	1 * Type-C analog headphone interface, supporting OTG; 1 * USB 3.0 supports M6 handheld microphone (with reserved UART serial port)	speaker	(2W) BOX speaker, compatible with dual speakers
Camera	Front camera: 16M; Rear camera: 64M; Night vision: 24M; Macro 2.0M(Optional 50M front camera)	button	5 buttons (power/fingerprint button, scan code button, PTT, volume button+-)
Flashlight	High brightness flash	Expand memory	Maximum support for 512GB TF card
NFC	Support	sensor	3D accelerometer, electronic compass, distance sensor, light sensor
Infrared remote control	Support		
receiver	1206 waterproof earpiece		
Wireless Communication			
5G	NR SA n1/n3/n20/n28/n41/n77/n78/n79 +5G NR NSA n1/n3/n41/n78/n79 +LTE-FDD B1/B3/B5/B7/B8/B20/B28 +LTE-TDD B34/B38/B39/B40/B41 +WCDMA B1/B5/B8 +GSM B2/B3/B5/B8	WIFI	WIFI6、Support(802.11 a/b/g/n/ac/ax)
		Bluetooth	BT 5.1
		GNSS	GPS, Beidou, GLONASS, Galileo

Environmental Specifications

Operation temperature	-20℃ ~ -60℃	Storage temperature	-40℃ ~ -70℃
Environmental humidity	5% RH-95% RH (non condensing)	Size	176.8*81.2*18.3mm
Degree drop gauge	6 sides can withstand multiple 1.5 meter drops (certified by 810G testing)	Weight	(The thickest part is 22.5mm) 390g (approximately) including battery, actual weight depends on the selected configuration module
Rolling test	1000 rounds of 0.5m rolling test	Colour	Black/Blue
Static electricity	Air discharge+-15KV, contact discharge+-8KV		
IP GRADE	IP67		

Standard

TYPE-C Cable,Adaptor,Hand Strap

Optional Modules

barcode scanner	Zebra SE4710/SE5500 (long-distance)	High precision positioning	Centimeter level, pure Beidou dual frequency RTK (optional configuration)
Charger	Optional	Thermal Imaging UHF	256 * 192 resolution Optional
DMR	U segment 2W		
ranging	Optional		

Product's Views:

