

PDS-GS1701B

17.0" Rugged Industrial Panel Display



Features:

- 17.0" TFT LED LCD screen
- Integrated capacitive touchscreen
- HDMI/VGA/DVI/USB(Touch Screen)
- Equipped with 6 function adjustment buttons
- Rugged all-aluminum construction for a wide range of applications
- Long life and high reliability
- Fast response time, no smear, no jitter
- Ultra-wide viewing angle for clear picture quality at large angles

Specifications:

Display

LCD Type	17.0" LCD	Display Scale	5:4
Resolution	1280*1024	Viewing Angle	170°(H)*170°(V)
Luminance	250 cd/m2 (Optional brightness)	Backlight Life	50000h

Touch Screen

Type	Integrated capacitive touchscreen	Hardness	≥6H
transmittance	≥85%		

Interface/switch

Display interface	1*HDMI, 1*VGA, 1*DVI	Outlet	DC5.5*2.5 power input(Optional aviation plug/terminal)
Button	Auto,Menu,Left,Right,Exit,ON/OFF	USB	1*USB(Touch Screen)

OSD Language

Language	Chinese, English, German, French, etc
----------	---------------------------------------

Power specifications

power input	12V DC(Optional 9-36V wide voltage module)
-------------	--

Environment

Shock Protection	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating Temp	-10℃~60℃
Vibration Protection	10g acceleration, 11ms period	Storage Temp	-20℃~70℃
Reliability	MTBF≥30000h; MTTR≤0.5h	Humidity	95% @40℃, no condensation
		IP Rating	Front panel IP65 (optional)

Mechanical

Dimension (WxHxD)	398mm*323.6mm*53.2mm	Mounting	VESA Mounting : 100mm*100mm/75mm*75mm
Weight	4.0kg/4.5kg(N.W./G.W.)		Embedded installation: 384mm*314mm
Color	black		
material	All metal fanless design		

Dimensions:

